

# Two Axle Transporter Trailer Specifications

## Two Models: Pay Load of 7 & 10 Tonne

Ref: 5068.2

<b>GVM</b>	9980kg (capable of approx. 7 tonne payload) <i>OR</i>
<b>GVM</b>	14000kg (capable of approx. 10 tonne payload)
<b>Tare</b>	2680 - 3100kg approx., pending final specification
<b>Axles</b>	Two Gigant brand 5500kg (or 7000kg) rated axles with drum brakes
<b>Chassis</b>	Profiled and fabricated in tensile steel
<b>Suspension</b>	Gigant brand air suspension
<b>Wheels</b>	8 only steel 17.5 x 6.75 wheels dual fitment
<b>Tyres</b>	8 only 215/70R17.5 tyres Triangle brand
<b>Brakes</b>	Load sensed full air brakes, with spring brakes (park brakes) on one axle. ABS braking on 1400kg trailer
<b>Toweye</b>	Flange mounted to suit 40mm Ringfeder type coupling
<b>Deck</b>	4.4m Flat Deck plus beaver tail. 2450mm wide. 32mm timber outside of deck with chequer plate in the centre of deck. Outside facing channel side rails with anchor points. Deck height 860mm 17°, air bags deflated 760mm 15°
<b>Storage</b>	Chain/toolboxes built in to area between chassis on the beaver tail and between chassis at the front of the deck
<b>Ramps</b>	Two aluminium manual ramps standard length 1950mm
<b>Landing Leg</b>	5 tonne rated wind up landing leg (empty load only)
<b>Lighting</b>	Hella LED combination tail lights with reverse lights. LED front and side marker lights to meet regulations
<b>Finish</b>	Chassis and body sandblasted and top coat painted
<b>On Road Costs</b>	Compliance, Registration, COF, and 1000km RUC included



Phone: 03 3489 510 or 0274 320 905

[More photos](#)





**ADAMS & CURRIE**  
**LIMITED**  
Road Transport Engineers

